



	OFT-20D-120
HORSEPOWER	20
OPERATING PRESSURE (PSI)	90-120 (LEAD PUMP) 80-110 (SECOND PUMP)
AIR DELIVERY (CFM)	60.0
CONTROL SYSTEM	MULTIPLE UNIT CONTROL - AUTO START/STOP
NOISE LEVEL (dB A)	78
AIR OUTLET (BALL VALVE)	3/4" NPT
OPERATING VOLTAGE	3 PHASE, 208-230V/460V, 60Hz
DIMENSIONS (LxWxH)	70" x 52" x 58"
APPROX. WT. (LBS.)	1260

NOTE: HIGH PRESSURE SPECS AVAILABLE UPON REQUEST

**NOTES:**

- 1) COMPRESSOR UNIT MUST BE INSTALLED IN A ROOM ON A FLAT FLOOR
- 2) COMPRESSOR IS AN AIR COOLED UNIT - ROOM TEMPERATURE MUST NOT EXCEED 104° F  
EXHAUST DUCTS OR VENTILATING FAN MUST BE INSTALLED IF ROOM TEMPERATURE EXCEEDS 104° F
- 3) PROVIDE ADEQUATE SPACE DURING INSTALLATION FOR NECESSARY MAINTENANCE AND REPAIRS  
ALLOW A MINIMUM OF 20" ON EACH SIDE AND 24" FROM TOP OF UNIT FROM WALLS
- 4) CARE MUST BE TAKEN TO INSURE COMPRESSOR UNIT DOES NOT INTAKE HOT AIR OR DUST
- 5) REFER TO INSTRUCTION MANUAL FOR ELECTRIC WIRING DIAGRAM
- 6) SPEC IS SUBJECT TO CHANGE WITHOUT NOTICE

**PROPRIETARY AND CONFIDENTIAL**  
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF **ANEST IWATA**. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF **ANEST IWATA** IS PROHIBITED.

UNLESS OTHERWISE SPECIFIED:	NAME	DATE	
DIMENSIONS ARE IN INCHES AND MILLIMETERS	DRAWN	AMM 4/28/20	
	CHECKED	AGH 4/30/20	
	ENG APPR.		
INTERPRET GEOMETRIC TOLERANCING PER:	MFG APPR.		<b>TITLE:</b> <b>OFT-20D-120</b> <b>OIL-FREE PISTON UNIT</b> <b>TANK MOUNT COMPRESSOR</b>
MATERIAL ASS'Y	Q.A.		
PART NO.	COMMENTS:		<b>SIZE</b> DWG. NO. REV <b>B</b> OFT-20D-120-R1 <b>1</b>
DO NOT SCALE DRAWING			SCALE: 1:20 WEIGHT: SHEET 1 OF 3