



SPECIFICATIONS

MODEL NO.	OFT-5-FRD-60
HORSEPOWER	5HP
OPERATING PRESSURE (psi)	90-120
AIR DELIVERY (cfm)	15.0
NOISE LEVEL (dB)	73
AIR OUTLET (BALL VALVE)	1/2" NPT
OPERATING VOLTAGE	3 Phase, 208-230/460V, 60Hz
DIMENSIONS (L x W x H)	68 x 33 x 54
APPROX. WT (lbs)	TBD

NOTES:

- 1) COMPRESSOR UNIT MUST BE INSTALLED IN A ROOM ON A FLAT FLOOR.
- 2) COMPRESSOR IS AN AIR COOLED UNIT - ROOM TEMPERATURE MUST NOT EXCEED 104°F. EXHAUST DUCTS OR VENTILATING FAN MUST BE INSTALLED IF ROOM TEMPERATURE EXCEEDS 104°F.
- 3) PROVIDE ADEQUATE SPACE DURING INSTALLATION FOR NECESSARY MAINTENANCE AND REPAIRS. ALLOW A MINIMUM OF 20" FROM EACH SIDE OF WALL, AND A MINIMUM OF 20" FROM FRONT OF UNIT, AND A MINIMUM OF 24" FROM TOP OF UNIT.
- 4) CARE MUST BE TAKEN TO INSURE COMPRESSOR UNIT DOES NOT INTAKE HOT AIR OR DUST.
- 5) REFER TO INSTRUCTION MANUAL FOR ELECTRIC WIRING DIAGRAM.
- 6) SPEC IS SUBJECT TO CHANGE WITHOUT NOTICE.

PROPRIETARY AND CONFIDENTIAL
 THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF ANEST IWATA Air Engineering Inc. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF ANEST IWATA Air Engineering Inc. IS PROHIBITED.

UNLESS OTHERWISE SPECIFIED:		NAME	DATE	ANEST IWATA Air Engineering Inc.	
DIMENSIONS ARE IN INCHES		DRAWN	AMM		2/19/20
		CHECKED			
		ENG APPR.			
		MFG APPR.			
		Q.A.			
		COMMENTS:			
NEXT ASSY	USED ON			TITLE: OFT-5-FRD-60 5HP OILLESS RECIPROCATING DRYER DUPLEX	
APPLICATION		DO NOT SCALE DRAWING		SIZE DWG. NO. REV C OFT-5(H)-FRD-60	
				SCALE: 1:12 WEIGHT: SHEET 1 OF 1	