

Oil Less Piston COMPRESSOR with Refrigerated Dryer



OFT - 7.5HP - 15HP



- ✓ Complete Air System
- ✓ Oil Less reciprocating piston compressor
- ✓ UL 508A rated control panel - NEMA 1
- ✓ Dynamically balanced for low vibration
- ✓ TEFC motor standard
- ✓ Intercoolers standard
- ✓ Easy maintenance
- ✓ No loss electric auto drain
- ✓ Composite Piston Technology with insulated wrist pin to reduce bearing heat
- ✓ High Efficiency refrigerated dryer Dew point 38F
- ✓ 0.3μ pre filter & 0.01μ final filter

Model	Horse Power (HP)	Pressure On/Off (PSI)	Flow Rate *1 (SCFM)	Air Outlet *2 (NPT)	Receiver (GAL)	Voltage (V)	Dimensions L x W x H (Reference)	Weight (lbs.)
OFT-5-FRD-60	5	90 - 120	15.0	1/2"	60	3ph/208-230V/460V/575V 60Hz	68 x 38 x 54	TBA
OFT-7.5-FRD-120	7.5		24.0		120		73 x 47 x 59	TBA
OFT-10-FRD-120	10		30.0	3/4"			TBA	
OFT-15-FRD-120	15		41.0		TBA			

*1 Air delivery is average discharge air volume at the maximum operating pressure converted into atmospheric pressure.

*2 Air outlet is connected to the ball valve.

The Air of Trust



Company ANEST IWATA Air Engineering, Inc.

Address: 9525 Glades Drive

West Chester, Ohio 45069

Phone: 513-755-5130

Toll Free 800-440-0282

Fax: 513-755-1889

Website: www.anestiwata.com