



	SLB-10
HORSEPOWER	10
MAX. OPERATING PRESSURE (PSI)	85-115
AIR DELIVERY (CFM)	29.7
AIR OUTLET	3/8" NPT
OPERATING VOLTAGE	3 PHASE, 208-230V/460V, 60Hz
DIMENSIONS (INCHES)	36" x 22" x 22"
APPROX. WT. (LBS.)	350

- NOTES:
- 1) COMPRESSOR UNIT MUST BE INSTALLED IN A ROOM ON A FLAT FLOOR
 - 2) COMPRESSOR IS AN AIR COOLED UNIT - ROOM TEMPERATURE MUST NOT EXCEED 104° F EXHAUST DUCTS OR VENTILATING FAN MUST BE INSTALLED IF ROOM TEMPERATURE EXCEEDS 104° F
 - 3) PROVIDE ADEQUATE SPACE DURING INSTALLATION FOR NECESSARY MAINTENANCE AND REPAIRS ALLOW A MINIMUM OF 20" ON EACH SIDE AND 24" FROM TOP OF UNIT FROM WALLS
 - 4) CARE MUST BE TAKEN TO INSURE COMPRESSOR UNIT DOES NOT INTAKE HOT AIR OR DUST
 - 5) REFER TO INSTRUCTION MANUAL FOR ELECTRIC WIRING DIAGRAM
 - 6) SPEC IS SUBJECT TO CHANGE WITHOUT NOTICE

PROPRIETARY AND CONFIDENTIAL
 THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF ANEST IWATA. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF ANEST IWATA IS PROHIBITED.

UNLESS OTHERWISE SPECIFIED:		NAME	DATE	
DIMENSIONS ARE IN INCHES		DRAWN	SDR 12/19/19	
		CHECKED	AMM 5/5/20	
		ENG APPR.		
		MFG APPR.		
		Q.A.		TITLE: SLB-10 OILFREE SCROLL UNIT TANK MOUNT BASE
		COMMENTS:		
MATERIAL	ASS'Y			
FINISH				SIZE B DWG. NO. SLB-10-R1 REV 1
DO NOT SCALE DRAWING		SCALE: 1:10 WEIGHT:		SHEET 1 OF 3