



	SLB-2	SLB-2H
HORSEPOWER	2	2
MAX. OPERATING PRESSURE (PSI)	115	145
AIR DELIVERY (CFM)	5.3	4.5
AIR OUTLET	3/8" NPT	
OPERATING VOLTAGE	1 PHASE, 115/208-230V, 60Hz 3 PHASE, 208-230/460V, 60Hz	
DIMENSIONS (L x W x H)	34" x 22" x 17"	
APPROX. WT. (LBS.)	140	

NOTES:

- 1) COMPRESSOR UNIT MUST BE INSTALLED IN A ROOM ON A FLAT FLOOR
- 2) COMPRESSOR IS AN AIR COOLED UNIT - ROOM TEMPERATURE MUST NOT EXCEED 104° F
EXHAUST DUCTS OR VENTILATING FAN MUST BE INSTALLED IF ROOM TEMPERATURE EXCEEDS 104° F
- 3) PROVIDE ADEQUATE SPACE DURING INSTALLATION FOR NECESSARY MAINTENANCE AND REPAIRS
ALLOW A MINIMUM OF 20" ON EACH SIDE AND 24" FROM TOP OF UNIT FROM WALLS
- 4) CARE MUST BE TAKEN TO INSURE COMPRESSOR UNIT DOES NOT INTAKE HOT AIR OR DUST
- 5) REFER TO INSTRUCTION MANUAL FOR ELECTRIC WIRING DIAGRAM
- 6) SPEC IS SUBJECT TO CHANGE WITHOUT NOTICE

PROPRIETARY AND CONFIDENTIAL
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF **ANEST IWATA**. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF **ANEST IWATA** IS PROHIBITED.

UNLESS OTHERWISE SPECIFIED:		NAME	DATE	ANEST IWATA Air Engineering Inc.
DIMENSIONS ARE IN INCHES		DRAWN	SDR	
		CHECKED	AMM	5/5/20
		ENG APPR.		
		MFG APPR.		
		Q.A.		
		COMMENTS:		TITLE: SLB-2 OILFREE SCROLL UNIT TANK MOUNT BASE
MATERIAL	ASS'Y			
FINISH				SIZE B DWG. NO. SLB-2-R1 REV 1
DO NOT SCALE DRAWING		SCALE: 1:10		WEIGHT: SHEET 1 OF 3