


	SLB-3	SLB-3H
HORSEPOWER	3	3
MAX. OPERATING PRESSURE (PSI)	115	145
AIR DELIVERY (CFM)	7.8	6.4
AIR OUTLET	3/8" NPT	
OPERATING VOLTAGE	3 PHASE, 208-230V/460V, 60Hz	
DIMENSIONS (INCHES)	34" x 22" x 17"	
APPROX. WT. (LBS.)	155	

NOTES:

- 1) COMPRESSOR UNIT MUST BE INSTALLED IN A ROOM ON A FLAT FLOOR
- 2) COMPRESSOR IS AN AIR COOLED UNIT - ROOM TEMPERATURE MUST NOT EXCEED 104° F EXHAUST DUCTS OR VENTILATING FAN MUST BE INSTALLED IF ROOM TEMPERATURE EXCEEDS 104° F
- 3) PROVIDE ADEQUATE SPACE DURING INSTALLATION FOR NECESSARY MAINTENANCE AND REPAIRS ALLOW A MINIMUM OF 20" ON EACH SIDE AND 24" FROM TOP OF UNIT FROM WALLS
- 4) CARE MUST BE TAKEN TO INSURE COMPRESSOR UNIT DOES NOT INTAKE HOT AIR OR DUST
- 5) REFER TO INSTRUCTION MANUAL FOR ELECTRIC WIRING DIAGRAM
- 6) SPEC IS SUBJECT TO CHANGE WITHOUT NOTICE

PROPRIETARY AND CONFIDENTIAL
 THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF ANEST IWATA. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF ANEST IWATA IS PROHIBITED.

UNLESS OTHERWISE SPECIFIED:		NAME	DATE	ANEST IWATA Air Engineering Inc. 	
DIMENSIONS ARE IN INCHES		DRAWN	SDR		4/30/20
		CHECKED	AMM		5/5/20
		ENG APPR.			
		MFG APPR.			
		Q.A.			
		COMMENTS:		SLB-3 OIL-FREE SCROLL UNIT TANK MOUNT COMPRESSOR	
MATERIAL	ASSY	SIZE	DWG. NO.		REV
PART NO.		B	SLB-3-R1		1
DO NOT SCALE DRAWING		SCALE: 1:10		WEIGHT:	
				SHEET 1 OF 3	