


	SLB-5	SLB-5H
HORSEPOWER	5	5
MAX. OPERATING PRESSURE (PSI)	115	145
AIR DELIVERY (CFM)	14.8	11.7
AIR OUTLET	3/8" NPT	
OPERATING VOLTAGE	3 PHASE, 208-230V/460V, 60Hz	
DIMENSIONS (LxWxH)	34" x 22" x 17"	
APPROX. WT. (LBS.)	175	

- NOTES:**
- 1) COMPRESSOR UNIT MUST BE INSTALLED IN A ROOM ON A FLAT FLOOR
  - 2) COMPRESSOR IS AN AIR COOLED UNIT - ROOM TEMPERATURE MUST NOT EXCEED 104° F EXHAUST DUCTS OR VENTILATING FAN MUST BE INSTALLED IF ROOM TEMPERATURE EXCEEDS 104° F
  - 3) PROVIDE ADEQUATE SPACE DURING INSTALLATION FOR NECESSARY MAINTENANCE AND REPAIRS ALLOW A MINIMUM OF 20" ON EACH SIDE AND 24" FROM TOP OF UNIT FROM WALLS
  - 4) CARE MUST BE TAKEN TO INSURE COMPRESSOR UNIT DOES NOT INTAKE HOT AIR OR DUST
  - 5) REFER TO INSTRUCTION MANUAL FOR ELECTRIC WIRING DIAGRAM
  - 6) SPEC IS SUBJECT TO CHANGE WITHOUT NOTICE

**PROPRIETARY AND CONFIDENTIAL**  
 THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF ANEST IWATA. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF ANEST IWATA IS PROHIBITED.

UNLESS OTHERWISE SPECIFIED:		NAME	DATE	ANEST IWATA Air Engineering Inc. 		
DIMENSIONS ARE IN INCHES	DRAWN	SDR	4/30/20			
	CHECKED	AMM	5/5/20			
	ENG APPR.					
	MFG APPR.					
INTERPRET GEOMETRIC TOLERANCING PER:		Q.A.		TITLE:		
MATERIAL	ASS'Y	COMMENTS:		<b>SLB-5</b> OIL-FREE SCROLL UNIT BASE MOUNT COMPRESSOR		
PART NO.			SIZE		DWG. NO.	REV
DO NOT SCALE DRAWING			<b>B</b>		<b>SLB-5-R1</b>	<b>1</b>
			SCALE: 1:10	WEIGHT:	SHEET 1 OF 1	