



SPECIFICATIONS	
MODEL NO.	SLT-10-FRD-80
HORSEPOWER	10HP
OPERATING POWER (psi)	85-115
AIR DELIVERY (cfm)	29.7
NOISELEVEL (dB)	75
AIR OUTLET (BALL VALVE)	1/2" NPT
OPERATING VOLTAGE	3 Phase, 208-230/460V, 60Hz
DIMENSIONS (L x W x H)	75 x 33 x 49
APPROX. WT (lbs)	TBD

- NOTES:
- 1) COMPRESSOR UNIT MUST BE INSTALLED IN A ROOM ON A FLAT FLOOR.
  - 2) COMPRESSOR IS AN AIR COOLED UNIT - ROOM TEMPERATURE MUST NOT EXCEED 104 °F. EXHAUST DUCTS OR VENTILATING FAN MUST BE INSTALLED IF ROOM TEMPERATURE EXCEEDS 104 °F.
  - 3) PROVIDE ADEQUATE SPACE DURING INSTALLATION FOR NECESSARY MAINTENANCE AND REPAIRS. ALLOW A MINIMUM OF 20" FROM EACH SIDE OF WALL, AND A MINIMUM OF 20" FROM FRONT OF UNIT, AND A MINIMUM OF 24" FROM TOP OF UNIT.
  - 4) CARE MUST BE TAKEN TO INSURE COMPRESSOR UNIT DOES NOT INTAKE HOT AIR OR DUST.
  - 5) REFER TO INSTRUCTION MANUAL FOR ELECTRIC WIRING DIAGRAM.
  - 6) SPEC IS SUBJECT TO CHANGE WITHOUT NOTICE.

**PROPRIETARY AND CONFIDENTIAL**  
 THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF ANEST IWATA Air Engineering Inc. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF ANEST IWATA Air Engineering Inc. IS PROHIBITED.

		UNLESS OTHERWISE SPECIFIED:		NAME	DATE	ANEST IWATA Air Engineering Inc.	
		DIMENSIONS ARE IN INCHES		DRAWN	AMM	2/21/20	TITLE: <b>SLT-10-FRD-80</b> 10HP SCROLL PUMP DRYER DUPLEX
				CHECKED			
				ENG APPR.			
				MFG APPR.			SIZE DWG. NO. REV <b>C</b> SLT-10(H)-FRD-80
				Q.A.			
		INTERPRET GEOMETRIC TOLERANCING PER:		COMMENTS:			SCALE: 1:12 WEIGHT: SHEET 1 OF 1
		MATERIAL ASS'Y					
NEXT ASSY	USED ON	FINISH					
		DO NOT SCALE DRAWING					