## Oil Less Scroll COMPRESSOR with Refrigerated Dryer



**SLT - 5HP - 10HP** 



- ∨ Complete Air System
- ✓ Oil Less scroll compressor
- ✓ Ultra quite and low vibration with scroll technology
- ✓ UL 508A rated control panel NEMA 1
- ✓ TEFC motor standard
- ✓ Intercoolers standard
- ✓ Easy maintenance
- ∨ No loss electric auto drain
- ✓ High Efficiency refrigerated dryer Dew point 38F
- $\vee$  0.3 $\mu$  pre filter & 0.01 $\mu$  final filter

Model	Horse Power (HP)	Pressure On/Off (PSI)	Flow Rate *1 (SCFM)	Air Outlet *2 (NPT)	Receiver (GAL)	Voltage (V)	Dimmensions L x W x H (Reference)	Weight (lbs.)
SLT-5-FRD-60	5	85 - 115	14.8	1/2''	60	3ph/208- 230V/460V/ 575V 60Hz	68 x 31 x 46	TBA
SLT-7.5-FRD-80	7.5		22.6		80		75 x 32 x 49	TBA
SLT-10-FRD-80	10		29.7					TBA

<sup>\*1</sup> Air delivery is average discharge air volume at the maximum operating pressure converted into atmospheric pressure.





Company ANEST IWATA Air Engineering, Inc.

Address: 9525 Glades Drive

West Chester, Ohio 45069

Phone: 513-755-5130 Toll Free 800-440-0282 Fax: 513-755-1889

Website: www.anestiwata.com

<sup>\*2</sup> Air outlet is connected to the ball valve.