PAR

Paint Booth Add



Contacts: Each Regional Sales Managers or Toll Free: 800-440-0282, Fax: 513-543-1079

INDUSTRY: Manufacturing

APPLICATION: Painting

PRODUCTS: SLTE-20D-120-T460

PRODUCT APPLICATION REPORT

DETAILS: The customer added a Paint Booth and Painting Operation into a strategic location in the plant, plant manufacturing process line. The quality of the finish paint is critical and requires high quality air. The customer did not believe the existing oil flooded plant air could be cleaned up effectively and did not want to add the Paint Operation demand to the existing system. The SLTE-20D-120 is a compact High Quality Air Oil Free tank mounted solution installed at the customer's Point of Use. Minimal piping was required. The dedicated system also provides redundancy in the duplex design and at only 69 dBa contributes minimally to the OA plant noise level.







Model SLTE-20D-120-T460 List Price \$32,980

SPECIFICATIONS: HORSEPOWER: 20 HP OPERATING PRESSURE: 75-115 PSI AIR DELIVERY: 59.4 CFM CONTROL SYSTEM: MULTI UNIT CONTROL - AUTO STOP/START NOISE LEVEL: 69 dBa AIR OUTLET: BALL VALVE 1" NPT POWER: 208-230-460V/3 PHASE/60Hz DIMENSIONS: 70" x 43" x 52" WEIGHT: 1,160 LBS.